



(12) **United States Patent**
Giorgi et al.

(10) **Patent No.:** **US 9,409,598 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **REPLACEABLE COUPLING CARTRIDGE**

(56) **References Cited**

(75) Inventors: **Marshall Giorgi**, Lodi, CA (US);
Danny Burgess, Stockton, CA (US)

(73) Assignee: **Rare Parts, Inc.**, Stockton, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/163,324**

(22) Filed: **Jun. 17, 2011**

(65) **Prior Publication Data**

US 2015/0251695 A1 Sep. 10, 2015

Related U.S. Application Data

(60) Provisional application No. 61/344,242, filed on Jun. 17, 2010.

(51) **Int. Cl.**
B62D 7/16 (2006.01)
F16C 11/00 (2006.01)
F16B 7/04 (2006.01)

(52) **U.S. Cl.**
CPC **B62D 7/16** (2013.01); **B62D 7/166** (2013.01);
F16C 11/00 (2013.01); **F16B 7/0413** (2013.01);
Y10T 403/68 (2015.01)

(58) **Field of Classification Search**
CPC B62D 7/08; B62D 7/16; B62D 7/20;
F16D 1/00; F16D 1/12; F16C 11/00; F16C
11/0609; F16C 11/0642; F16C 11/0619
See application file for complete search history.

U.S. PATENT DOCUMENTS

2,848,260	A *	8/1958	Moskovitz	403/11
2,900,196	A *	8/1959	Nienke	280/86.756
3,059,950	A *	10/1962	Hedges	403/74
3,061,344	A *	10/1962	Gray et al.	403/125
3,239,256	A *	3/1966	Carter	403/68
3,791,006	A *	2/1974	Robinson	29/283
4,256,413	A *	3/1981	Abe	403/282
4,568,216	A *	2/1986	Mizusawa et al.	403/143
4,613,250	A *	9/1986	Laucus	403/11
4,704,043	A *	11/1987	Hackman et al.	403/56
5,885,022	A *	3/1999	Maughan et al.	403/135
6,550,120	B1 *	4/2003	Maughan et al.	29/401.1
6,644,671	B1 *	11/2003	Maughan et al.	277/635
8,757,648	B1 *	6/2014	Winter	280/93.511
2003/0133745	A1 *	7/2003	Molenaar	403/143

* cited by examiner

Primary Examiner — Daniel Wiley

(57) **ABSTRACT**

A universal replaceable cartridge for coupling together members of a linkage assembly. The cartridge includes a generally cylindrical body having first and second ends and first and second surfaces. A first threaded portion is formed on the first surface of the cylindrical body adjacent the first end and a second threaded portion is formed on the second surface of the cylindrical body adjacent the second end. The threaded portions allow the cartridge to be threadedly attached to first and second members of the linkage assembly.

2 Claims, 3 Drawing Sheets

